


2

1


PART NUMBER	DIM. A
PS180B-0131GG-P	.125"
PS180B-0132GG-P	.180"
PS180B-0133GG-P	.215"

REVISIONS		
REV.	DESCRIPTION	DATE
A	INITIAL RELEASE	9/21/2020

B




B



A

- NOTE:
1. INSULATOR MATERIAL: GLASS FILLED POLYESTER
 2. FLAMABILITY RATING: UL94V-0
 3. OPERATING TEMP: -55C TO +125C
 4. ACCEPTS -.015-.021 DIAMETER PIN
 5. SHELL MATERIAL: BRASS ALLOY C36000, 1/2 HARD
 6. SHELL PLATING 10µ MIN. OVER NICKEL, 100µ MIN
 7. CONTACT MATERIAL: BeCu
 8. CONTACT PLATING: 10µ MIN. OVER NICKEL, 100µ MIN

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ADAPTERS-PLUS INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ADAPTERS-PLUS IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:		NAME	DATE	 Adapters-Plus Inc. Ph: 209-839-0200 web: www.adapt-plus.com
DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± .1 ANGULAR: MACH ± .1 TWO PLACE DECIMAL ± .01 THREE PLACE DECIMAL ± .005		DRAWN	AM	
INTERPRET GEOMETRIC TOLERANCING PER: MATERIAL FINISH		CHECKED	SB	09/21/20
		ENG APPR.		
		MFG APPR.		
DO NOT SCALE DRAWING		Q.A.		
		COMMENTS:		
SIZE	DWG. NO.	REV		
A	PS180B-013XGG-P	A		
SCALE: 2:1	WEIGHT:	SHEET 1 OF 1		

A

2

1